

N5200PRO

Simply Storage – Storage Simply
Thecus - The Storage Experts

HDD:
5x 3.5" SATA II HDD, Hot-swappable

eSATA port:
1 x eSATA connector for capacity expansion

USB port:
3 x USB A type (Host mode) / 1 x USB B type (Client mode)

Ethernet ports:
N5200 PRO - 2 x Gigabit RJ-45 Connector
N5200R PRO - 1 x Gigabit RJ-45 Connector
4 x Gigabit switch

Link aggregation:
Supports 2 port, Load Balancing (N5200 PRO only)

LCD Control Panel:
For basic configurations and status display

Network File Protocols:
Microsoft Windows (SMB) / Apple Filing Protocol (AFP 3)
Network File System (NFS v3) / File Transfer Protocol (FTP)
Hyper Text Transfer Protocol (HTTP) /
Secure File Transfer Protocol (SFTP) /
Hyper Text Transfer Protocol (HTTPs)

Authentication:
Microsoft NT Domain Controller (PDC*)
Microsoft Active Directory Authentication (AD*)

Network Client Type:
Microsoft Windows NT/2000/XP/2003
Unix/Linux/BSD
MAC OS X, OS 9, OS 8.6

Network Configuration:
Fast Ethernet Address
Dynamic IP Address

Disk Management:
Power Management (Disk idle spin-down)
Disk Status Monitoring (S.M.A.R.T.)

RAID:
RAID 0, 1, 5, 6, 10, and JBOD
Supports multiple RAID modes – Users can create multiple RAID on one system.

Auto Raid Aid:
Hot Swapable
Hot Spare
Disk Roaming
RAID Migration
RAID Expansion
Disk Capacity Supported : 80/120/160/200/250/300/400/500/750/1000 GB

Taiwan HQ:
15F, No. 199, Sec. 1, Simai 5th Rd.,
Saijih City, Taipei County, Taiwan (R.O.C.)
TEL: +886-2-2653-0000
E-mail: sales@thecus.com

Thecus Technology Corp. All rights reserved.
Thecus, Thecus logo, and trademarks of Thecus Technology Corp.
Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Apple and Apple OS X are registered trademarks of Apple Computer, Inc.

ISCSI Target:
Configurable block level access

Folder Management:
Share Folder Level Permission
File Level Permission
Disk Protection

Quota Management:
Share Folder Quota Control

System Management:
Thecus Backup Utility (Microsoft Windows XP/2000/MAC OS X)
Thecus Nasify

System Management:
Web GUI
Multilingual Support (English, French, German, Italian, Traditional Chinese, Simplified Chinese, Japanese, Korean, Spanish)
NT LAN Manager
Wake-On-LAN
Schedule Power On/Off – For better power management

Email Notification:
Buzzer Notification

USB:
Supported USB Devices
USB Printer
External USB Flash disk
USB IEEE 802.11 b/g/n dongle w/ AP mode support **

Setup Utility:
Windows 2000 / XP / 2003
MAC OS X

Operating Environment:
CE, FCC, BSMI, C-Tick, RoHS Compliant

Dimension:
230 x 190 x 230 mm (H x W x D)

Power:
Lockable Disk Tray

Operating Environment:
0 ~ 40°C
20 ~ 95% Relative Humidity (non-condensing)

Power Supply:
Server-rated AC Power Supply
100~240VAC, 50~60 Hz, Auto detect

*Design and specifications are subject to change without prior notice.

Germany office:
Gebensteinerstr 17 D-76277
Ettlingen, Germany
E-mail: support@thecus.de

US office:
1500 10th Street, Suite 1000
Arlington, VA 22209, USA
E-mail: support-us@thecus.com

05-2007